

SPECIFICATION SHEET

=====

SMPS based BATTERY CHARGER (Auto Float Boost)

MODEL : BCOE1210A

INPUT

- * I/P : 230V AC, 1-Ph, 40-60Hz
- * Range : 150-300V AC
- * Fuse Protection.
- * I/P MOV
- * Soft Start

OUTPUT

- * Nominal Battery Voltage : 12V DC
- * Float Voltage : 13.5V
- * Boost Voltage : 14.4V
- * Current : 10A
- * Line Regulation : +/- 1%
- * Load Regulation : +/- 1%
- * Ripple : +/- 1% (P-P)
- * Protections : a) Over load Protection auto recovery type.
b) Short circuit Protection auto recovery type.
d) Reverse Polarity by relay.
- * Current Limit

ENVIRONMENTAL

- * Operating temperature 0 to 50⁰ C.
- * Humidity : < 95% Rh
- * IP 20 Protection

GENERAL

- * Potential Free Contact - Alarm contact for output fail
- * Isolation : Input to Output - 1.5KV
Input to Earth - 1.5KV
Output to Earth- 500V
- * MTBF : 50K Hrs to MIL

INDICATIONS LED

- : a) Input OK
- b) Output ON
- c) Battery Reverse
- d) Float
- e) Boost
- f) Low Batt

MECHANICAL

- * Dimension : approx. 180(W) X 125(D) X 100(H)mm.
- * Cooling type : Fan
- * Weight : approx. 1 Kg