

**BATTERY CHARGER Model: 3BC7230A**

It is modular system and consists of 2 modules of 72V 15A & 1 common controller unit.

**SPECIFICATIONS:-**

- \* Input : 180-270V AC Single phase, 47-63Hz
- \* Battery Voltage : 72V DC
- \* Float Voltage - 81V (adj)
- \* Boost Voltage - 86.4V (adj)
- \* Current : 30A (adj. by pot 15-30A)
- \* Auto/ Manual selection switch shall be provided on front side of panel.
- \* Float/ Boost selection switch shall be provided on front side of panel.
- \* Potentiometer for Current, float & boost adjustment provided on front side.
- \* LED indications : Float , Boost on front side of panel.
- \* Input MCB
- \* Dimension : approx. 355w x 475d x 425h mm
- \* Net weight : approx. 25 kgs.

---

**Specifications of 72V 15A (each individual unit) :--**

**I/P : 180 - 270V AC Single Phase**

- \* With Built in Power Factor Correction 0.99
- \* Fuse Protection.
- \* I/P MOV
- \* Soft Start

**O/P : 72V DC 15A**

- \* Voltage : 72V
- \* Current : 15A
- \* Line & Load Regulation : Less Than 1%
- \* Ripple & Noise : Less Than 1% (P-P)
- \* Over Load Protection auto recovery type.
- \* Short Circuit Protection auto recovery type.
- \* Over Voltage Protection Latching type.
- \* Over Temperature Protection auto recovery type.

- \* Current limit
- \* Operating Temperature 0 to 50<sup>0</sup> C.
- \* I/O Isolation : 2 KV
- \* Alarm Contact - Potential Free Contact for output fail
- \* Fan Cooled
- \* Enclosure Type : IP20

### **LED INDICATIONS OF 72V 15A MODULE :**

- 1) Input OK - Green LED
- 2) Output OK-Green LED
- 3) Input Under or Over Voltage (U/O)-Red LED
- 4) Output Over Voltage (OVP)-Red LED
- 5) Output Over Load (O/L)-Red LED
- 6) Output Over Temp ( O/T)-Red LED

### **Optional :**

- Load & Battery Terminal separate