

SPECIFICATION SHEET

=====

SWITCH MODE POWER SUPPLY**MODEL** : PS1201A**INPUT**

* I/P : 230V AC, 1-Ph
* Frequency : 47-63Hz
* Range : 180-270V AC
* Fuse Protection. : Yes
* Soft Start : Yes
* AC current : 1.5A@230V AC

OUTPUT

* Nominal Voltage : 12V DC
* Voltage Range : 12-15V
* Rated Current : 1A
* Line Regulation : +/- 1%
* Load Regulation : +/- 1%
* Ripple Max : +/- 1% (P-P)
* Noise Max : +/- 1% (P-P)
* Protections
: a) Overload Protection auto recovery type:102-105%
: b) Short circuit protection auto recovery type:Yes
: c) Over Voltage Protection Latching type:105-110%
* Current Limit : Yes

ENVIRONMENTAL

* Operating temperature 0 to 50⁰ C.
* Humidity : < 95% Rh
* IP 20 Protection

GENERAL

* Isolation : Input to Output - 1.5KV
: Input to Earth - 1.5KV
: Output to Earth- 500V
* MTBF : 50K Hrs to MIL

MECHANICAL

* Dimension : 100 X 65 X 40H mm - with box
: 90 X 45 X 30H mm - open type
* Cooling type : Natural
* Weight : 0.2Kg