

## AC TO DC POWER SUPPLIE

### SPECIFICATION

<b>MODEL</b>	PS2420A..
<b>INPUT</b>	
I/P	110V AC, 1-Ph
Frequency	47-63Hz
Range	90-135V AC
Fuse Protection.	Yes
I/P MOV	Yes
Soft Start	Yes
Inrush current	92A@230V AC
AC Current	
Leakage Current	<5mA@230V AC
<b>OUTPUT</b>	
Nominal Voltage	24V DC
Voltage Range	24-28V
Rated Current	20A
Line Regulation	+/- 1%
Load Regulation	+/- 1%
Ripple Max	+/- 1% (P-P)
Noise Max	+/- 1% (P-P)
Protections	a) Overload Protection auto recovery type:102-105% b) Short circuit protection auto recovery type:Yes c) Over Voltage Protection Latching type:105-110%
Current Limit.	Yes
Start up time	3sec
Hold up time	35ms@230V AC
Transient response	--
<b>ENVIRONMENTAL</b>	
Operating temperature upto 50 <sup>0</sup> C.	
Humidity	< 95% Rh
IP 21 Protection	
<b>GENERAL</b>	
Isolation	Input to Output – 1.5KV Input to Earth – 1.5KV Output to Earth- 500V
MTBF	50K Hrs to MIL
Efficiency	80%
<b>INDICATIONS LED</b>	a) Input OK b) Output OK c) Output OVP

## **MECHANICAL**

Dimension	235W X 195D X 100H mm
Cooling type	Fan cooled – exhaust ??
Weight	3 Kgs

## **OPTIONAL**

Redundancy by external diode.  
Potential Free Contact – Alarm contact  
Programmable by external signal – voltage & current  
Remote ON/OFF  
With Digital Voltmeter & Currenmeter  
Over Temperature Protection