

AC TO DC POWER SUPPLIE**SPECIFICATION****MODEL**

PS1204A

INPUT

I/P 230V AC, 1-Ph
Frequency 47-63Hz
Range 90-270V AC
Fuse Protection. Yes
I/P MOV Yes
Soft Start Yes
Inrush current 23A@230V AC
AC Current
Leakage Current <5mA@230V AC

OUTPUT

Nominal Voltage 12V DC
Voltage Range 10-15V
Rated Current 4A
Line Regulation +/- 1%
Load Regulation +/- 1%
Ripple Max +/- 1% (P-P)
Noise Max +/- 1% (P-P)
Protections

Current Limit. Yes
Start up time 750ms
Hold up time 37ms@230V AC
Transient response --

a) Overload Protection auto recovery type:102-105%
b) Short circuit protection auto recovery type:Yes
c) Over voltage Protection Latching type:105-110%

ENVIRONMENTAL

Operating temperature upto 50⁰ C.
Humidity < 95% Rh
IP 21 Protection

GENERAL

Isolation Input to Output – 1.5KV
Input to Earth – 1.5KV
Output to Earth- 500V
MTBF 50K Hrs to MIL
Efficiency 75%

INDICATIONS LED

a) Input OK
b) Output OK
c) Output OVP

MECHANICAL

Dimension

135W X 90D X 50H mm

Cooling type

Natural

Weight

0.5 Kg

OPTIONAL

Redundancy by external diode.